

Specifications:

- Dimensions of the plank: **upon clients' needs:**
 - Thickness – from 15 to 21 mm;
 - Width – from 50 to 100 mm;
 - Length – from 300 to 1000 mm.
- Species available: **European Oak / Honey Locust (Gleditsia triacanthos);**
- Grades available: **Select (A), Nature (B) and Rustic – see the photos below**
- Profile: **Tongue & Groove on all 4 sides;**
- Edges: **Square**
- Surface: **unfinished**
- Wood Moisture Content: **10 +/-2%;**
- Weight: **approximately 16kg per m2;**
- Packing: **Sealed packs / max 50m2 per pallet;**
- Manufacturing Standards: according to the country's standards;
- Durability: **Serviceable Life Can be sanded repeatedly (up to 10 times)(22mm);**

Grades:

Select (A): Uniformly coloured structure, the presence of healthy knots fused to 2 mm, formed by the natural growth of the tree. Not allowed sapwood and rough differences in the colour of the wood.



Oak, Select



Gleditsia Select

Nature (B):

Uniformly coloured structure caused by natural growth. Sapwood is allowed on the parquet floor and firmly fused knots to 6 mm.



Oak, Nature



Gleditsia Nature

Rustic: It is allowed colouring on the floor caused by natural growth, sapwood to 15% and firmly fused knots to 20 mm.



Oak, Rustic



Gleditsia Rustic

Recommendations:

- Acclimatisation: **2-3 days in unopened packs;**
- Underfloor Heating: **Not recommended;**
- Instalation: **Glued to the sub-floor (recommended) or Nailed;**
- Sanding: **recommended after installation (subject to used glue);**

The factory of TIVIS:

- Based in 2004 in Shumen, Bulgaria;
- Uses first class of wood material;
- Production according clients' standards;
- High level of performance;
- Export of its production in several countries in Europe: Germany, Italy, France, Spain, Hungary and Romania.



For more information, please visit: www.tivis.net or call: 00359 899 163 870.